## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau

[WIPO]

[Bar Code]

(43) International Publication Date

October 6, 2005 (10/06/2005)

**PCT** 

(10) International Publication Number

WO 2005/093164 A1

- (51) International Patent Classification<sup>7</sup>: B06B 1/16


E02D 3/074

- (21) International Application No.: PCT/EP2005/002456
- (22) International Filing Date: March 9, 2005 (03/09/2005)
- (25) Language in which the international application was originally filed: German
- (26) Language in which the international application is published: German
- (30) Priority Data: 10 2004 014 375.7 March 17, 2004 (03/17/2004) DE
- (71) Applicant (for all designated states except the U.S.): HYDAC SYSTEM GMBH [DE/DE]; Industriegebiet, 66280 Sulzbach/Saar (DE).
- (72) Inventor; and
- (75) Inventor/Applicant (U.S. only): KRICK, Martin [DE/DE]; Parallelstrasse 16, 66538 Neunkirchen (DE).

- (74) Representative: BARTELS UND PARTNER; Lange Strasse 51, 70174 Stuttgart (DE).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TY, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European Patent (AT, BE, GB, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, HU, IE, IT, LU, MC, NL, PL,

[continued on next page]

## (54) Title: DEVICE FOR CONTROLLING AND ACTUATING A VIBRATING MECHANISM



(57) Abstract: The device for controlling and actuating a vibrating mechanism, particularly in tampers, comprises a hydraulic pump (12) that drives a hydrzulic motor (18), which interacts with the vibrating mechanism (10) while being a part of a hydraulic circuit (16) to which a pressure regulator (22) is connected in the secondary branch (20) and can be controlled by a hydraulic switching device (24). This configuration provides a purely hydraulic solution that does not require electrical current for controlling and switching off the vibrating mechanism.

[Fortsetzung auf der nächsten Seite]

PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, Published: With International Search Report.

codes and the other abbreviations to the Guidance Notes on Codes and Abbreviations in the front section of each

Reference is made for an explanation of the two-letter regular PCT Gazette edition.

CARLOS LINGUILANDE GOP?